

SIZE RANGE

BENDER FERNDORF

T mm Ø/Size		6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25,4	
		0,236	0,275	0,315	0,354	0,393	0,433	0,472	0,511	0,551	0,590	0,629	0,669	0,708	0,748	0,787	0,826	0,866	0,905	0,944	1,000	
20"	508,0																					
22"	558,0																					
24"	609,6																					
26"	660,4																					
28"	711,2																					
30"	762,0																					
32"	812,8																					
36"	914,4																					
40"	1016,0																					
44"	1117,6																					
48"	1219,2																					
52"	1320,8																					
56"	1422,4																					
60"	1524,0																					
64"	1625,6																					
68"	1727,2																					
72"	1828,8																					

YIELD POINT

up to 675 N/mm ² X 80 L555MB	up to 600 N/mm ² X 70 L485MB	up to 535 N/mm ² X 60/X 65 L415MB/ L450MB	up to 460 N/mm ² X 52/X 56 St 52.0/ S 355 L360MB/ StE 385.7	up to 375 N/mm ² X 42/X 46 St 44.2/ S 275 L290MB StE 320.7	up to 290 N/mm ² API Gr. B St 37.0/ S 235 ASTM Grades
--	--	--	--	---	---

Further quality-/size combinations available on request